



UltraFix Grout

Coloured, latex modified cement grout for ceramic, glass mosaic, porcelain and non-moisture sensitive natural stones tiles

PACKAGING AND COLOURS

UltraFix Grout is available in 20 kg sacks.

STANDARDS

BS 5980 - Cementitious Adhesives and Grouts

BS EN 13888 CG2.

COVERAGE AND YIELD

1 kg is sufficient for approximately 4 m² using standard 150 x 150 mm tiles.

20 kg bag mixed with 6.6 L of water yields approximately 15 L

DESCRIPTION

UltraFix Grout is a fine coloured latex modified powder which, when mixed with water, gives a smooth, easily applied creamy paste for clean grouting of ceramic tiles. It sets to a decorative water-resistant finish

ADVANTAGES

- Water-resistant (suitable for swimming pools)
- Available in a range of colours
- Resistant to cracking in joints up to 6mm wide
- Ideal for internal and exterior applications
- Formulated for Middle East conditions
- Resistant to mould growth

UltraFix Grout is a blend of hydrophobic cement, fillers and organic additives.

TYPICAL PROPERTIES

Mixed density @25°C	1777 kg/m ³
Compressive Strength ASTM C109	>20 N/mm ²
Flexural Strength ASTM C580	>6 N/mm ²

APPLICATION GUIDELINES

Allow at least 24 hours between fixing tiles and grouting. Mix grout powder with water to give a smooth, thick consistency.

Leave to stand for 15 minutes before using. Apply to tile joints with a squeegee, brush or sponge. Remove surplus grout with a damp sponge. When grouting is completed, polish tiles with a dry cloth.

WATER ADDITION

6.6 L per 20 kg bag

WATCH POINTS

Certain types of tile may stain when in contact with coloured cement grouts, it is therefore advisable to consult the tile manufacturer and carry out trials before use.

For natural stone tiles susceptible to staining, please contact Gulf Additive Factory Technical Services.

STORAGE AND SHELF LIFE

Store out of direct sunlight, clear of the ground on pallets protected from rainfall. Avoid excessive compaction.

Shelf life is 12 months when stored as above, in original, unopened bags



UltraFix Grout

HEALTH AND SAFETY

As with all chemical products, care should be taken during use and storage to avoid contact with eyes, mouth, skin and foodstuffs (which may also be tainted with vapour until product is fully cured). Treat splashes to eyes and skin immediately. If accidentally ingested, seek immediate medical attention. Reseal containers after use.

QUALITY AND CARE

All products originating from Gulf Additive Factory, Qatar facility are manufactured under a management system independently certified to conform to the requirements of the quality, environmental and occupational health safety standard ISO 9001 and ISO 14001.

GAF-QAT-UF G-11-22-Rev01

STATEMENT OF RESPONSIBILITY: *The technical information and application advice given in this GAF publication are based on the present state of our best scientific and practical knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by law. The user is responsible for checking the suitability of products for their intended use.*

NOTE: *Field service where provided does not constitute supervisory responsibility. Suggestions made by GAF either orally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they, and not GAF are responsible for carrying out procedures appropriate to a specific application.*

Gulf Additive Factory (GAF)
St. 703 Mesieed Industrial area
P.O. Box: 2050 Doha – Qatar
C.R.No : 102054
Tel : +974 44169957

